

734D Series for DS-3 and DS-4

75 Ohm Cross-Connect Cable

Product Construction

Conductor:

- 20 AWG silver-plated copper

Insulation:

- Gas-injected foamed PE (O.D.: 0.146")

Shield:

- Foil: Aluminum
- Braid: 85% tinned copper

Jacket:

- Flame-retardant PVC

Temperature/Voltage Rating

- 75° C/300 V

Packaging

- 1000' wood reels

Applications

- Interconnect and cross-connecting central offices
- Plenum cable is also available upon request

Compliances

- UL and c(UL) Type CMR



CMR (Non-Plenum)

PRODUCT NUMBER	CONDUCTORS	HFA PRODUCT NUMBER
7340201	1	CO20C0012410
7340201T	1 + 22 AWG Tracer	ZO20C0022010
7340202	2	CO20C0022410
7340203	3	CO20C0032410
7340206	6	CO20C0061110
7340208	8	CO20C0082410
7340209	9	CO20C0092410
7340212	12	CO20C0122410
7340216	16	CO20C0162410

Data subject to change without notice.

ELECTRICAL CHARACTERISTICS

SRL 5-90 MHz (dB MIN.)	DC RESISTANCE (OHMS/KFT NOM.)	SHIELD DC RESISTANCE (OHMS/KFT NOM.)	NOMINAL CAPACITANCE (pF/ft)	NVP %
30	10.1	5.6	17.3	80

ATTENUATION (NOMINAL)

MHz/SIGNAL	dB/100ft	dB/100m
0.772	0.24	0.79
CEPT1	0.25	0.82
CEPT2	0.50	1.64
5	0.54	1.77
10	0.75	2.46
CEPT3	0.98	3.21
DS3	1.15	3.77
STS1	1.21	3.97
44.736	1.65	5.41
50	1.70	5.58
CEPT4	2.01	6.59
STS3	2.19	7.18
100	2.69	8.82
DS4	2.94	9.64
200	3.58	11.74

Data subject to change without notice.