



IEEE 1580 Type P — MOR® Polyrad® XT-125 Flexible Unarmored Cables

- Table of Contents 3
- Unarmored Flexible Single Conductor Power Cable 4, 5
- Unarmored & Sheathed Flexible Single Conductor Power Cable 6, 7
- Unarmored Flexible Multi Conductor Control Cable – 18 & 16 AWG 8, 9
- Unarmored Flexible Multi Conductor Low-Voltage Power Cable – 16 AWG 9
- Unarmored Flexible Multi Conductor Control Cable – 14 AWG, 12 AWG & 10 AWG 10-12
- Unarmored Flexible Multi Conductor Low-Voltage Power Cable – 14 AWG, 12 AWG & 10 AWG 12
- Unarmored Flexible Multi Conductor Power Cable – 2, 3, 4, & 5 Conductors 13-15
- Unarmored Flexible Variable Frequency Drive (VFD) Power Cable – 3 Conductor 16, 17
- Unarmored Flexible Paired Signal Cable, Individually/Overall Shielded – 20 AWG – 14 AWG 18-20
- Unarmored Flexible Triad Signal Cable, Individually/Overall Shielded – 18 AWG & 16 AWG 21, 22

IEEE 1580 Type P — MOR® Polyrad® XT-125 Flexible Armored & Sheathed Cables

- Table of Contents 23
- Armored & Sheathed Flexible Single Conductor Power Cable 24, 25
- Armored & Sheathed Flexible Multi Conductor Control Cable – 18 AWG & 16 AWG 26, 27
- Armored & Sheathed Flexible Multi Conductor Control Cable – 14 AWG, 12 AWG & 10 AWG 28-30
- Armored & Sheathed Flexible Multi Conductor Power Cable – 2, 3, 4, & 5 Conductors 31-33
- Armored & Sheathed Flexible Variable Frequency Drive (VFD) Power Cable – 3 Conductor 34, 35
- Armored & Sheathed Flexible Paired Signal Cable, Individually/Overall Shielded – 20 AWG – 14 AWG 36-38
- Armored & Sheathed Flexible Triad Signal Cable, Individually/Overall Shielded – 18 AWG & 16 AWG 39, 40

IEEE 1580 Type P Resources

- Table of Contents 41
- Standard Conductor Chart 42
- Standard Color Code Chart 43
- 95°C Ampacity 44
- 100°C Ampacity 45
- 110°C Ampacity 46
- 125°C Ampacity 47
- Approvals/Certifications 48
- Part Number Index 49-53