



Offshore and
Marine Shipboard
Cables

IEEE 1580 Type P MOR[®] Polyrad[®] XT-125 Armored & Sheathed



**Flexible Multi Conductor Control
Armored & Sheathed
14 AWG, 12 AWG & 10 AWG
600V/1000V**



CATALOG NUMBER (T-75126)	# OF CORES	COND. SIZE (AWG)	NOMINAL CABLE DIAMETER		NET WEIGHT		AMPACITIES ¹ 45°C AMBIENT-SINGLE BANKED			
			INCHES	mm	LBS/1000 FT	kg/km	95°C	100°C	110°C	125°C
326130	2	10	0.675	17.14	338	503	47	49	52	64
279220	3	10	0.700	17.78	369	549	39	41	44	49
279230	4	10	0.750	19.05	469	698	31	33	35	39
356910	5	10	0.810	20.57	550	819	31	33	35	39
356920	6	10	0.855	21.72	616	917	31	33	35	39
316620	7	10	0.855	21.72	662	985	27	29	31	34
356930	8	10	0.910	23.11	737	1097	27	29	31	34
356940	10	10	1.135	28.83	1024	1524	19	21	22	25
356950	12	10	1.165	29.59	1137	1692	19	21	22	25

Note: Dimensions and weights are nominal; subject to industry tolerances.

¹Reference Ampacity section