

Jacks, outlets and patch panels

Category 6/7 – 250/600 MHz



ELine™ NOVUM patch panel, 24 ports

483 mm (= 19") x 44 mm x 150 mm (WxHxD)



ELine 600® GG45 patch panel, 24 ports 4 x 6

19", 1 U, 480 x 44 x 135 mm (WxHxD)

Mounting depth: 155 mm

Product description:

For a maximum of

- 24 x GG45 or 24 x RJ45 MLS/MLU or mixed media
- Front panel: light grey RAL 7035
- Extremely easy to mount
- Traction relief on back
- Can be earthed via screw connection

Product description:

- Without components
- Steel design, can be equipped with up to 24 ELine 600® GG45 outlets, 4 x sextuple mounting clips, snap-in assembly of outlets, clip-on cable guide with large-surface shield contacting, insertable marking strips, front panel
- Scope of delivery: Modular patch panel, marking strips
- Colour: light grey, RAL 7035

Article number: 9ZK00024

Pcs. per packing unit: 1

Article number: 9ZE20012, fixed – 9ZE20010, telescopic

Pcs. per packing unit: 1



ELine 600® GG45 dual outlet insert, long

50 x 50 x 20 mm (WxHxD)

Mounting depth: 35 mm

Inclination: 45°



ELine 600® GG45 dual outlet insert, short

50 x 50 x 20 mm (WxHxD)

Mounting depth: 35 mm

Inclination: 45°

Product description:

- Without components
- For concealed and underfloor mounting
- Can be equipped with up to 2 ELine 600® GG45 jacks, screwless mounting of jacks
- Connecting point for an additional terminal clamp for traction relief or earthing
- Suitable for 50 x 50 frames
- Pure white, RAL 9010
- Scope of delivery: central panel (50 x 50), snap-in mounting ring, marking window (delivery without cover frame)

Article number: 9ZE20005

Pcs. per packing unit: 8

Product description:

- Without components
- For concealed and cable duct mounting
- Can be equipped with up to 2 ELine 600® GG45 jacks, screwless mounting of jacks
- Suitable for 45 mm round hole frames and 50 x 50 frames
- Pure white, RAL 9010
- Scope of delivery: central panel (50 x 50), snap-in mounting ring, marking window (delivery without cover frame)

Article number: 9ZE20004

Pcs. per packing unit: 8

Jacks, outlets and patch panels



ELine 250® ML dual outlet insert

86 x 86 mm (WxH)



ELine 250® ML dual outlet insert

80 x 80 mm (WxH)

Product description:

For a maximum of

- 2 x RJ45 ELine™ MLS (9ZK00023) or 2 x RJ45 ELine™ MLU (9ZK00002)
- or mixed media
- Pearl white, RAL 9016

2 models: 45° – Article number: 9ZK00006

Pcs. in packing unit: 12

90° – Article number: 9ZK00007

Pcs. in packing unit: 12

Product description:

For a maximum of

- 2 x RJ45 ELine™ MLS (9ZK00023) or 2 x RJ45 ELine™ MLU (9ZK00002)
- or mixed media
- Pure white, RAL 9010

2 models: 45° – Article number: 9ZK00004

Pcs. in packing unit: 12

90° – Article number: 9ZK00005

Pcs. in packing unit: 30



ELine 250® ML single outlet insert

45 x 45 mm (WxH)



ELine 250® ML single module for outlet insert

22.5 x 45 mm (WxH)

Product description:

For a maximum of

- 1 x RJ45 ELine™ MLS (9ZK00023) or 1 x RJ45 ELine™ MLU (9ZK00002)
- Pure white, RAL 9010

Model: 90° – Article number: 9ZK00011

Pcs. in packing unit: 12

Product description:

ELine™ single outlet insert for dual outlet

- 1 x RJ45 ELine™ MLS (9ZK00023) or 1 x RJ45 ELine™ MLU (9ZK00002)
- Pure white, RAL 9010

Model: 90° – Article number: 9ZK00010

Pcs. in packing unit: 24

Jacks, outlets and patch panels



ELine 600® GG45 Cat. 7 patch cord/work area cord



ELine 600® GG45 assembly tool

Product description:

- 4P (ML F6-90 S/F flex, 7KS70014
- A end equipped with 4-pair GG45 plug
- B end equipped with 4-pair GG45 plug
- Assignment: 1/1
- Colour of bending protection sleeve GG45/GG45: black
- Application: Cat. 7 services

Article number: 9KN01010 – 1.0 m

9KN01020 – 2.0 m

9KN01030 – 3.0 m

9KN01050 – 5.0 m

Pcs. per packing unit: 1

Product description:

- Assembly tool or simple, safe moulding of the ELine 600® GG45 jack

Article number: 9ZKE20006

Pcs. per packing unit: 1



ELine 250® ML assembly tool

Product description:

- For simple, safe connection of the jacks ELine 250® RJ45 MLS/MLU

Article number: 9ZK00009

Pcs. per packing unit: 1

